

Family Group: Accelerated Production	Item #: QS-GR2	Scale: To Page
Product Name: 2' Standard Rail	Drawn By: DEEP	Version: September 2017

IMPORTANT NOTES

- The client and/or owner shall be responsible for all quantities and dimensions including the verification of, and coordination with field conditions.
- The client and/or owner shall verify all critical dimensions and conditions of existing construction that relate to this project prior to manufacturing.
- Cogan must be notified in writing of any elements found to be inconsistent or not compatible with the details indicated by these approval drawings.
- The client and/or owner shall be responsible for the building classification on all construction and warrant that all construction shall be governed by the latest edition of the state building code (including any revisions or addendas) and/or with any other applicable code or requirements of all authorities having jurisdiction.
- Verify all dimensions and details carefully.
- For installation support, please call Cogan at 1-800-567-2642.
- Press 1 (for material handling) then press 4 (installation support).
- Or press 0 to speak with an operator and ask for "installation support".

LEAD TIMES & SHIPPING

- Dollar Limit for Accelerated Production orders is \$5,000
- Please allow up to 48 hours turnaround time for all Accelerated Production quote requests.
- Ship dates are set only after the receipt of your Official Purchase Order. Please indicate your requested ship date when submitting your Official Purchase Order.

PRODUCT SPECIFICATIONS

- Guardrails are 12" high, made with ASTM a607 grade 50 corrugated steel.
- End Plate: 3/16" thick steel plate punched with two $\varnothing \frac{9}{16}$ " oblong holes.
- Overall Length: 19"
- Overall Height: 12 1/2"
- Overall Width: 3 1/4"
- Finish: Powder Coat Safety Yellow
- Installing Cogan's guardrail system at a minimum of 12" distance will help ensure the safety of your protected area due to rail deformation caused by collision.
- Based on 4000 PSI concrete, Cogan recommends anchors $\varnothing 5/8$ " x 4 1/2" (wedge type).

